

Double lock model / Modelo doble cierre

Ref. 5050: nickel / niquelado

Ref. 5235: black oxide / pavonado

Complies with NIJ Standard – 0307.01 /
Cumple el test NIJ Standard – 0307.01



Type of link / Tipo de unión	Chain / Cadena
Key / Llave	Standard
Manufacturation / Fabricación	Riveted / Remachado
Mechanism / Mecanismo	Double lock treated / Doble cierre tratado
Toothed / Dentado	Double / Doble
Weight / Peso	335 grs
Length / Longitud	238 mm
Minimum opening / Apertura mínima	50 mm
Minimum inside perimeter / Perímetro interior mínimo	165 mm
Maximum inside perimeter / Perímetro interior máximo	200 mm
Locking positions / Posiciones de cierre	20
Material	Steel K-70 / Acero K-70
Rockwell B hardness / Dureza Rockwell B	HRB-92
Thickness folded / Grosor Plegado	20 mm

Hinged model / Modelo bisagra

Ref. 5232: nickel / niquelado

Ref. 5233: black oxide / pavonado

Complies with salt spray test /
Cumple las pruebas de la niebla salina



Type of link / Tipo de unión	Hinge / Bisagra
Key / Llave	Standard
Manufacturation / Fabricación	Riveted / Remachado
Mechanism / Mecanismo	Double lock treated / Doble cierre tratado
Toothed / Dentado	Double / Doble
Weight / Peso	340 grs
Length / Longitud	215 mm
Minimum opening / Apertura mínima	50 mm
Minimum inside perimeter / Perímetro interior mínimo	165 mm
Maximum inside perimeter / Perímetro interior máximo	200 mm
Locking positions / Posiciones de cierre	20
Material	Steel K-70 / Acero K-70
Rockwell B hardness / Dureza Rockwell B	HRB-92
Thickness folded / Grosor Plegado	20 mm